

٥

Ē



Þ



## FIG. 3

## START

ACCORDING TO INPUT SPECIFICATION FOR VIEWING-DESIRED BROADCAST PROGRAM, REGISTER PIDS OF PSI (NIT, PAT, PMT, AND ECM), PID OF ES (IMAGE AND AUDIO), AND PID OF SI (EIT) FOR VIEWING-DESIRED BROADCAST PROGRAM INTO FIRST NECESSARY PID TABLE CORRESPONDING TO FIRST TS

S2 ALLOW USER TO PERFORM OPERATION FOR DISPLAYING BROADCAST PROGRAM TABLE

S3 SWITCH TO TRANSPONDER INCLUDING SI (Schedule EIT) COMPOSING BROADCAST PROGRAM TABLE

→ ACTIVATE SECOND TUNER AND DEMODULATOR SECTION, ACOUIRE SECOND TS INCLUDING BROADCAST PROGRAM TABLE, AND OUTPUT IT TO SECOND TS.PACKET EXTRACTING SECTION

S4 REGISTER PID OF EIT (Schedule EIT) IN SECOND NECESSARY PID TABLE

S5 EXTRACT TS PACKET INCLUDING PID (PID OF Schedule EIT) REGISTERED IN SECOND NECESSARY PID TABLE FROM SECOND TS, AND OUTPUT IT AS NECESSARY PACKET NECESP TO TS.PACKET OVERWRITING SECTION

COMPARE FIRST TS WITH FIRST NECESSARY-PID TABLE, ACOUIRE UNNECESSARY-PACKET DETECTION INFORMATION Unneces, AND OUTPUT IT TO TS.PACKET OVERWRITING SECTION

BUFFER FIRST TS, UNNECESSARY-PACKET DETECTION INFORMATION Unneces, AND NECESSARY PACKET NecesP

OVERWRITE NECESSARY PACKET NecesP. EXTRACTED FROM SECOND TS. TO UNNECESSARY-PACKET AREA TS. OF FIRST TS SPECIFIED BY UNNECESSARY-PACKET DETECTION INFORMATION Unneces, AND BUFFER OVERWRITTEN RESULT AS SINGLE CUSTOM TRANSPORT STREAM (CTS)INFORMATION Unneces, AND OUTPUT IT TO TS.PACKET OVERWRITING SECTION

S8 SERIALLY OUTPUT CTS TO TS. SEPARATING SECTION

END

PSI: PROGRAM SPECIFIC INFORMATION

NIT : NETWORK INFORMATION TABLE
PAT : PROGRAM ASSOCIATION TABLE

PMT: PROGRAM MAP TABLE

ECM : ENTITLEMENT CONTROL MESSAGE

ES : ELEMENTARY STREAM

(IMAGE SIGNAL, AUDIO SIGNAL, DATA

SIGNAL)


SI : BROADCAST-PROGRAM LAYOUT


INFORMATION


TSP: TRANSPORT STREAM PACKET


PID : PACKET IDENTIFIER


EIT : EVENT INFORMATION TABLE















**S4** 

**S6** 





ACCORDING TO INPUT SPECIFICATION FOR VIEWING-DESIRED BROADCAST PROGRAM, REGISTER PIDS OF PSI (NIT, PAT, PMT, AND ECM), PID OF ES (IMAGE AND AUDIO), AND PID OF SI (EIT) FOR VIEWING-DESIRED BROADCAST PROGRAM INTO FIRST NECESSARY PID TABLE CORRESPONDING TO FIRST TS

ALLOW USER TO PERFORM OPERATION FOR DISPLAYING BROADCAST PROGRAM TABLE

IMAGE-RECORDING-DESIRED BROADCAST
PROGRAM IS INCLUDED IN TS INCLUDING
VIEWING BROADCAST PROGRAM?

ACOUIRE PID OF PMT FOR IMAGE-RECORDING-DESIRED BROADCAST PROGRAM FROM PAT IN FIRST TS

YES

NO

BASED ON PID OF PMT, RECEIVE PMT FOR IMAGE-RECORDING-DESIRED BROADCAST PROGRAM, AND ACOUIRE PIDS OF ECM, IMAGE SIGNAL, AND AUDIO SIGNAL THEREFROM

BASED ON PIDS OF ECM, IMAGE SIGNAL, AND AUDIO SIGNAL, RECEIVE ECM, IMAGE SIGNAL, AND AUDIO SIGNAL FOR IMAGE-RECORDING-DESIRED BROADCAST PROGRAM


S10 EXTRACT ALL PIDS INCLUDED IN FIRST TS, AND REGISTER ALL OF EXTRACTED PIDS IN EXISTING PID TABLE

ACCORDING TO ANALYSIS OF NIT ACOUIRED FROM FIRST TS, SWITCH TO TRANSPONDER INCLUDING IMAGE-RECORDING-DESIRED BROADCAST PROGRAM ACTIVATE SECOND TUNER AND DEMODULATOR SECTION, ACOUIRE SECOND TS INCLUDING IMAGE-RECORDING-DESIRED BROADCAST PROGRAM, AND OUTPUT IT TO SECOND TS.PACKET EXTRACTING SECTION

REGISTER PID OF PAT AND PID OF EIT IN SECOND NECESSARY PID TABLE (REGISTRATION OF P2 AND P7)


EXTRACT TS PACKET INCLUDING PIDS (PIDS OF PAT AND EIT) REGISTERED IN SECOND NECESSARY PID TABLE FROM SECOND TS, AND OUTPUT IT AS NECESSARY PACKET NecesP TO IDENTICAL-PACKET-IDENTIFIER DETERMINING SECTION AND PACKET-IDENTIFIER CONVERTING SECTION

## FIG. 11



S23





OUTPUT NECESSARY PACKET NecesP OF PAT, EIT, AND PMT, AND THOSE OF POST-PID CONVERSION TO TS.PACKET OVERWRITING SECTION

COMPARE FIRST TS WITH FIRST NECESSARY-PID TABLE, ACOUIRE UNNECESSARY-PACKET DETECTION INFORMATION Unneces, AND OUTPUT IT TO TS.PACKET OVERWRITING SECTION (P20, P22, AND P29)

BUFFER NECESSARY PACKET NecesP INCLUDING FIRST TS, UNNECESSARY-PACKET DETECTION INFORMATION Unneces, AND THOSE OF POST-PID CONVERSION

OVERWRITE NECESSARY PACKET NecesP, EXTRACTED FROM SECOND TS, TO UNNECESSARY-PACKET AREA TS<sub>00</sub> OF FIRST TS SPECIFIED BY UNNECESSARY-PACKET DETECTION INFORMATION Unneces (P20 ← P32 (PAT)) (P22 ← P10 (PMT) (P24 ← P37 (EIT)).

BUFFER NEW SINGLE CTS (CUSTOM TRANSPORT STREAM)


S27 SERIALLY OUTPUT CTS TO TS. SEPARATING SECTION


ACQUIRE PIDS OF ECM, IMAGE SIGNAL, AND AUDIO SIGNAL, FOR IMAGE-RECORDING-DESIRED BROADCAST PROGRAM FROM PMT IN SECOND TS INCLUDING IMAGE-RECORDING-DESIRED BROADCAST PROGRAM


REGISTER PIDS OF ECM, IMAGE SIGNAL, AND AUDIO SIGNAL IN SECOND NECESSARY PID TABLE (ADDITIONAL REGISTRATION OF P11, P12, AND P13)


EXTRACT TS PACKET INCLUDING PIDS (PIDS OF PAT, EIT, PMT, ECM, IMAGE SIGNAL, AND AUDIO SIGNAL) REGISTERED IN SECOND NECESSARY PID TABLE FROM SECOND TS, AND OUTPUT IT AS NECESSARY PACKET NecesP TO IDENTICAL-PACKET-IDENTIFIER DETERMINING SECTION AND PACKET-IDENTIFIER CONVERTING SECTION






























4) j





į









FIG. 27



a 6/ #

E . > 6

j e

FIG. 28

